



CATALOGUE
2024



ADESIVI





TRADITIONS, QUALITY, INNOVATIONS

ADESIVI is one of the most recognizable brands in the self-adhesive tape market, whose goal is to provide innovative, high-quality and affordable products for the needs of construction, industry and commerce. Behind the trademark is the 30-year experience and professionalism of the Elplast Ltd. team. The company is successfully engaged in the production of self-adhesive tapes and polyethylene packaging, constantly expanding its product portfolio. Elplast produces products under its own brands, as well as for private labels to external contractors. Over the years, we have established ourselves as a reliable partner of a number of large industrial enterprises, retail chains in the construction sector and distributors in the country and neighbouring countries. With its ADESIVI brand the company presents several product groups on the market: paper tapes, packaging tapes, self-adhesive assembly tapes, specialized tapes. The pursuit of innovative solutions and direct communication with consumers and brand partners are the basis of the continuous renewal and expansion of ADESIVI's product portfolio.

ADESIVI BASIC PAPER TAPE

TYPE 205

Economy class self-adhesive paper tape with good adhesive properties. Universal product for construction and general use. Suitable for painting, ground coating, plasters, screeds, pasting various surfaces during construction and finishing works.

Colour: white



CHARACTERISTICS

Total tape thickness	145 microns
Tensile strength	3.7 kg/cm
Bonding to steel	230 g/cm
Indoor stay recommended	24 hours
Heat resistance	60°C / 30 minutes
Type of glue	Acrylic-Solvent

SIZES

code	30300174	30300194	30300122	30300123	30300124
width	19mm	25mm	30mm	38mm	50mm
length	45m	45m	45m	45m	45m
pc/carton	60	48	32	30	24

The product can be made with specific parameters.



ADESIVI BASIC PAPER TAPE

TYPE 210

High initial tack, low-adhesive self-adhesive tape for interior construction. It is characterized by easy and quick sticking on different surfaces. Suitable for painting, contouring, plastering, and pasting details. Easy to apply and remove without leaving traces of glue.

Colour: ivory



CHARACTERISTICS

Total tape thickness	130 microns
Tensile strength	3.2 kg/cm
Bonding to steel	230 g/cm
Indoor stay recommended	12 hours
Heat resistance	40°C / 30 minutes
Type of glue	Synthetic rubber (Hotmelt)

SIZES

code	30300181	30300182	30300125	30300126	30300127
width	19mm	25mm	30mm	38mm	48mm
length	45m	45m	45m	45m	45m
pc/carton	60	48	40	32	24

The product can be made with specific parameters.



ADESIVI PAPER TAPE

TYPE 216

Universal tape for general use in construction and industry. Suitable for painting, contouring, gluing and packaging. Does not damage even the most delicate surfaces when removing. It is characterized by an excellent degree of adhesion and a perfect contouring. This multifunctional paper tape is extremely convenient to work with, easy to apply and remove without leaving traces of glue.

Colour: ivory



CHARACTERISTICS

Total tape thickness	125 microns
Tensile strength	3.44 kg/cm
Bonding to steel	230 g/cm
Indoor stay recommended	72 hours
Heat resistance	60°C / 30 minutes
Type of glue	natural rubber

SIZES

code	303000449	303000412	303000450	303000452	303000545
width	19mm	25mm	30mm	38mm	48mm
length	45m	45m	45m	45m	45m
pc/carton	60	48	40	32	24

The product can be made with specific parameters.



ADESIVI PAPER TAPE

TYPE 220

Universal waterproof tape suitable for auto repair, industrial packaging, general use. Type 220 is used as a go to solution for carton packaging in the industry. Multifunctional paper tape convenient to work with, easy to apply and remove without traces of glue. It is characterized by a high degree of adhesion to metal, glass, plastic. Excellent contouring. Suitable for working with all types of automotive paints and thinners.

Colour: brown



CHARACTERISTICS

Total tape thickness	125 microns
Tensile strength	3.93 kg/cm
Bonding to steel	234.5 g/cm
Indoor stay recommended	up to 3 days
Heat resistance	80°C / 20 minutes
Type of glue	natural rubber

SIZES

code	303000455	303000456	303000486	303000457	303001110
width	19mm	25mm	30mm	38mm	50mm
length	45m	45m	45m	45m	45m
pc/carton	60	48	32	30	24

The product can be made with specific parameters.



ADESIVI AUTO PAPER TAPE

TYPE 225

High-grade strong adhesive waterproof tape for auto repair. Suitable for working with all types of automotive paints and solvents. Easy to apply and remove without leaving any traces of glue. It is characterized by a high degree of adhesion on metal, plastic, tape on tape. Provides excellent contouring.

Colour: yellow



CHARACTERISTICS

Total tape thickness	130 microns
Tensile strength	3.20 kg/cm
Bonding to steel	230 g/cm
Indoor stay recommended	up to 5 days
Heat resistance	100°C / 20 minutes 80°C / 40 minutes
Type of glue	natural rubber

SIZES

code	30300144	30300140	3030000161	30300158	304000315
width	19mm	25mm	30mm	38mm	50mm
length	45m	45m	45m	45m	45m
pc/carton	60	48	40	32	24

The product can be made with specific parameters.



PRECISE TAPE FOR PAINTING – WASHI

TYPE 252

High-grade self-adhesive tape for a perfect contour made of Japanese rice paper. UV stabilized up to 60 days. Low-adhesive tape for excellent results in precise contouring when painting non-standard shapes and curves. Easy to apply and remove without leaving any traces of glue. Does not damage even the most sensitive surfaces when removing. High UV rays, moisture and solvents resistance. The thin extra-strong paper combined with the ultra-sensitive adhesive makes it the ideal choice for the most responsible applications in painting and decorating.



CHARACTERISTICS

Total tape thickness	80 microns
Tensile strength	4 kg/cm
Bonding to steel	130 g/cm
Indoor stay recommended	up to 90 days
Heat resistance	120°C / 60 minutes
Type of glue	acrylic

SIZES

code	30300183	30300184	30300185	30300186	30300187
width	19mm	25mm	30mm	38mm	48mm
length	45m	45m	45m	45m	45m
pc/carton	60	48	40	32	24

The product can be made with specific parameters.



PRINTED PAPER TAPE

Paper tape with an advertising inscription is an ecological, safe and effective solution for branding transport packages. It gives the product an identity, makes the packaging recognizable and helps build the corporate image. The use of paper tapes helps to protect the environment, as they are subject to full recycling and reuse of the obtained raw material.

Main advantages of paper tape with an advertising inscription:

- Recyclable
- Environmental friendliness - removing plastic from packaging
- Excellent adhesion to uneven surfaces
- High load resistance
- Easy to use - eliminates the need for cutting tools
- Contributes to the aesthetic appearance of Kraft paper packaging



PACKAGING TAPE WITH ADVERTISING INSCRIPTION

Packaging tape with an advertising inscription (logo) is a quick and effective solution for branding transport packages. It gives the product an identity, makes the packaging recognizable and helps build the corporate image.

It is suitable for sealing cartons, packages, sticking pallets, postal items, etc.

- Production according to an individual design
- Type of adhesive layer - acrylic, hotmelt, solvent
- Carrier tape - BOPP
- Silent uncoiling
- Excellent adhesion to a variety of surfaces



ACRYLIC PACKAGING TAPE

TYPE 100

Packaging tape with a water-based adhesive layer for manual and automated use. Suitable for packing light and medium-heavy cartons. Tapes with water-based glue are characterized by high UV rays, aging and high temperatures resistance. Good adhesive properties, tear resistance and the ability to work outdoors make it a universal solution for sealing cardboard and other packaging.

Colour: transparent, brown, yellow, blue, black, green, red, white



CHARACTERISTICS

Total tape thickness	40 microns
Tensile strength	3.5 kg/cm
Bonding to steel	220 g/cm
Temperature range after sticking	from 5°C to 40°C
Storage temperature	from 15°C to 35°C
Type of glue	acrylic

SIZES

code	303000001	303000011	303000116	303000004	304000167
width	38mm	48mm	75mm	48mm	48mm
length	60m	60m	60m	100m	900m
pc/carton	42	36	24	36	6

The product can be made with specific parameters.



ECO SOLVENT PACKAGING TAPE

TYPE 300

Packaging tape with a water-based adhesive layer and synthetic resins for manual and automated use. Suitable for packing light and heavy cartons. It is characterized by high resistance to UV rays, aging and high temperatures. Good adhesive properties, tear resistance and the ability to work outdoors make it a universal solution for sealing cardboard and other packaging. The thick adhesive layer and the wider operating temperature range compared to ordinary acrylic tapes make it stand out as a reliable and environmentally friendly solvent substitute.

Colour: transparent



CHARACTERISTICS

Total tape thickness	47 microns
Tensile strength	4.5 kg/cm
Bonding to steel	230 g/cm
Temperature range after sticking	from -5°C to 40°C
Working temperature range	from 10°C to 40°C
Type of glue	synthetic resins

SIZES

code	303000109	303001221	303000667	304000221
width	48mm	75mm	48mm	48mm
length	60m	60m	100m	900m
pc/carton	36	24	36	6

The product can be made with specific parameters.



HOT MELT PACKAGING TAPE

TYPE 425

Packaging tape for manual and automated use. Suitable for packing light to medium weight cartons. The aggressive adhesive properties and easy uncoiling of the hot melt adhesives ensure easy, reliable and long-lasting gluing on corrugated boxes and other paper packaging. Self-adhesive tapes with hot melt glue are characterized by extremely low odour, good resistance to moisture and to extremely low temperatures (up to -25 degrees), which makes it a preferred choice in the food industry.

Colour: transparent



CHARACTERISTICS

Total tape thickness	42 microns
Tensile strength	4 kg/ cm
Bonding to steel	500 g/cm
Temperature range after sticking	from -25°C to 30°C
Storage temperature	from 15°C to 30°C
Type of glue	synthetic rubber

SIZES

code	303000204	303000117	30400022
width	48mm	48mm	48mm
length	60m	100m	900m
pc/carton	36	36	6

The product can be made with specific parameters.



PACKAGING TAPE - XTAPE

TYPE 450

Packing tape made from bi-oriented polypropylene carrier for hand and machine use. The extremely aggressive hybrid adhesive makes it suitable for sealing all types of cardboard boxes, polyethylene packaging, etc. It is characterized with high resistance to extremely low and high temperatures, UV rays, aging and moisture.

Preferred choice for operation in sub-zero temperatures down to (-25 degrees). For frozen foods, fruits, vegetables. The innovative hybrid adhesive layer of X tape provides it with the advantages of all other types of tape. The best and most economical solvent substitute.

Colour: transparent, blue, brown



CHARACTERISTICS

Total tape thickness	45 микрона (28 мк носец слой, 17 мк лепило)
Tensile strength	4.2 kg/cm
Bonding to steel	500 g/cm
Temperature range after sticking	from -25°C to 45°C
Storage temperature	from 15°C to 35°C
Type of glue	hybrid glue

SIZES

code	303000916	303000954	30300101
width	48mm	48mm	48mm
length	60m	100m	900m
pc/carton	36	36	6

The product can be made with specific parameters.



PACKAGING TAPE SOLVENT

TYPE 500/501

High-end self-adhesive tape for manual and automated use. Suitable for packing light and heavy loads. The glue based on natural rubber guarantees trouble-free and stable adhesion even on the most difficult surfaces: recycled cardboard packaging, rough and glossy cartons. Tape solvent type 500 is the most universal and reliable solution among tapes in the packaging and transportation processes. Extremely resistant to low and high temperatures. Designed to work in adverse conditions - high humidity, dustiness, temperature extremes.

Colour: transparent, brown, white



CHARACTERISTICS

Total tape thickness	45 microns
Tensile strength	4.5 kg/cm
Bonding to steel	250 g/cm
Temperature range after sticking	from -25°C to 60°C
Storage temperature	from 15°C to 35°C
Type of glue	natural rubber

SIZES

code	303001349	30300175	30300141	304000217
width	48mm	75mm	48mm	48mm
length	60m	60m	100m	900m
pc/carton	36	24	36	6

The product can be made with specific parameters.



PACKAGING TAPE

TYPE 825 SILENT

Silent packaging tape with a water-based adhesive layer for manual use. Suitable for packing light and medium-heavy cartons when working in a quiet environment. Tapes with water-based glue are characterized by high resistance to UV rays, aging and high temperatures. Good adhesive properties, tear resistance and the ability to work outdoors make it a universal solution for sealing cardboard and other packaging.

Colour: transparent, brown



CHARACTERISTICS

Total tape thickness	43 microns
Tensile strength	4.0 kg/cm
Bonding to steel	230 g/cm
Temperature range after sticking	from 5°C to 40°C
Storage temperature	from 15°C to 35°C
Type of glue	acrylic

SIZES

code	304000154			
width	48mm	75mm	48mm	48mm
length	60m	60m	100m	900m
pc/carton	36	24	36	6

The product can be made with specific parameters.



TAPE FOR THE REPAIR OF POLYETHYLENE GREENHOUSES

TYPE 790

Professional self-adhesive tape made of high-quality polyethylene base coated with pressure-sensitive acrylic adhesive. Intended for repairing torn or damaged sections of greenhouses, for insulation or sealing around their doors or windows. Thanks to UV stabilization it does not burn under the influence of sunlight. Excellent resistance to moisture, aging, chemicals and aggressive temperature conditions. The film's good balance between adhesive strength and elasticity ensures ease of use and good adaptability to uneven surfaces.

Colour: transparent



CHARACTERISTICS

Total tape thickness	150 microns
Tensile strength	26 N/cm
Bonding to steel	3.5 N/cm
Working temperature	from 0°C to 70°C
Storage temperature	from 12°C to 25°C

SIZES

code	3030000211	3030000212
width	50mm	100mm
length	20m	20m
pc/carton	36	18

The product can be made with specific parameters.



TEXTILE HOBBY TAPE

TYPE 700

Polyethylene tape reinforced with textile threads for universal use. Suitable for many different applications - bandaging, fastening, retention, protection, repair work. It is characterized by exceptional strength and adhesive strength. A universal and quick solution for repair work in the home, office, garden, indoors and outdoors. Resistant to different climatic conditions. Colour: silver, black, blue, green, red, yellow



CHARACTERISTICS

Total tape thickness	180 microns
Tensile strength	4 kg/ cm
Bonding to steel	900 g/ cm
Heat resistance	to 80°C
Type of glue	synthetic rubber (hotmelt)

SIZES

code	3030000177	3030000178
width	48mm	48mm
length	10m	25m
pc/carton	36	36

The product can be made with specific parameters.



GAFFER TEXTILE TAPE

TYPE 750

High-strength textile tape with a matte finish. It is widely used in the entertainment industry (film and theatre sets, photography, radio and television equipment), industry, construction and transport. The matte finish makes it an excellent choice where light reflection is a problem. It is resistant to ultraviolet rays, abrasion and wear; adheres well to uneven surfaces. Good tensile strength, withstands tough applications that can cause stress on the tape. Easy to unroll and tear crosswise by hand, leaves no traces of glue after peeling.



CHARACTERISTICS

Total tape thickness	300 microns
Tensile strength	980 N/100 mm
Bonding to steel	78.8 N/100 mm
Temperature range after sticking	up to 93°C for 30 minutes
Storage temperature	from 15°C to 35°C
Type of glue	natural rubber

SIZES

code	3030000209	3030000210
width	48mm	48mm
length	10m	25m
pc/carton	36	36

The product can be made with specific parameters.

REINFORCED TAPE WITH FIBERGLASS THREADS

MONOFILAMENT TAPE TYPE 720

Self-adhesive tape with exceptional strength and strong adhesion - reinforced with longitudinally placed fibres of fiberglass. Suitable for packing, reinforcing, tying and tightening of heavy loads and objects. It cannot be broken by hand, a cutting tool is required to break it. UV and water resistant. Suitable for outdoor and indoor use.



CHARACTERISTICS

Total tape thickness	130 microns
Tensile strength	25 kg/cm
Bonding to steel	1000 g/cm
Storage temperature	from 15°C to 35°C
Type of glue	synthetic rubber

SIZES

code	3030000213	3030000214
width	25mm	48mm
length	25m	25m
pc/carton	36	36

The product can be made with specific parameters.



REINFORCED TAPE WITH FIBERGLASS THREADS

CROSS FILAMENT TAPE TYPE 72I

Reinforced self-adhesive tape, bidirectionally reinforced with fiberglass for extreme loads. It is used for banding, palletizing, fastening, packing and fastening of heavy loads and objects. Exceptional strength performance and good adhesion to multiple surfaces including metal, plastic and fibreboard. Resistant to UV rays, tearing, scratching, moisture, splitting both longitudinally and transversely. Withstands harsh conditions of transportation and handling. It is characterized by low extensibility, it cannot be torn by hand. Suitable for indoor and outdoor installation.



CHARACTERISTICS

Total tape thickness	130 microns
Tensile strength	27 kg/cm
Bonding to steel	1000 g/cm
Storage temperature	from 15°C to 35°C
Type of glue	synthetic rubber

SIZES

code	3030000215	3030000216
width	25mm	48mm
length	25m	25m
pc/carton	36	36

The product can be made with specific parameters.



DOUBLE-SIDED ADHESIVE TAPE

TYPE 900 - TRANSPARENT CARRIER

80 mk and total thickness with the liner 150 mk. Adhesive based on synthetic rubber. Suitable for industrial and general use, resistant to low temperatures after installation. It is quickly and easily attached to various surfaces - metal and plastic details, glass, cardboard, laminate, posters, and signs. In many industries, double-sided adhesive tapes provide the ability to securely bond multiple surfaces.



CHARACTERISTICS

Total tape thickness	150 microns
Tensile strength	2.5 kg/cm
Bonding to steel	1300 g/cm
Type of glue	synthetic rubber

SIZES

code	30300149	30300193	30300150	30300188	30300194
width	19mm	25mm	30mm	38mm	50mm
length	10m	10m	10m	10m	10m
pc/carton	60	48	40	32	24

The product can be made with specific parameters.



IXPE MOUNTING DOUBLE-SIDED ADHESIVE TAPE

TYPE 950

Double-sided adhesive mounting tape with a carrier layer of polyethylene foam and acrylic solvent-based adhesive. Suitable for indoor applications requiring high strength and durability of the connection. Designed for long-lasting and stable bonding of heterogeneous materials with different linear expansion - glass, metal, plastic, wood, painted surfaces. It is widely used in the installation of mirrors, cable ducts, hangers, signs, posters, cornices, panels, refrigerators, in cars and others. The combination of strength, adaptability and excellent adhesion make these tapes a quick and easy method of permanent bonding with high strength and long-term bond durability.

Colour: white



CHARACTERISTICS

Total tape thickness	1 mm
Tensile strength	1 kg/cm
Bonding to steel	1000 g/cm
Temperature range after sticking	from 0°C to 60°C
Storage temperature	from 15°C to 35°C
Type of glue	acrylic solvent

SIZES

code	303000189	303000190
width	19mm	25mm
length	5m	5m
pc/carton	36	36

The product can be made with specific parameters.



VHB MOUNTING DOUBLE-SIDED ADHESIVE TAPE

TYPE 960

Double-sided adhesive tape with high elasticity and polyethylene protector. Suitable for applications requiring high strength and durability of the connection. Resistant to moisture, vibrations, high and low temperatures, UV rays, chemical agents and others. VHB tape glue is highly pressure sensitive, which ensures immediate and strong adhesion. Long-lasting and stable bonding of heterogeneous materials with different linear expansion - metal, glass, varnished wood, painted surfaces, most plastics. Suitable for industrial and general everyday use. A proven alternative to mechanical fasteners (bolts, screws, rivets), assembly silicones and adhesives.

Colour: transparent



CHARACTERISTICS

Total tape thickness	1 mm
Tensile strength	0.8 kg/cm
Bonding to steel	1100 g/cm
Working temperature range	from -40°C to +93°C
Type of glue	acrylic

SIZES

code	30300191	30300192
width	19mm	25mm
length	5m	5m
pc/carton	36	36

The product can be made with specific parameters.





www.adesivi.bg
www.elplast-bg.com



+359 887 62 72 93



office@elplast-bg.com

